

TECHNICAL INFORMATION

PRODUCT : HSVLT-W : GLOSS CLEAR PVC LABEL

VSCLTG60/PE-05/GAWHOG58

SURFACE **VSCLTG60**

Type **Gloss transparent soft PVC Film**

PHYSICAL PROPERTIES

Basic Weight 78 ± 5 g / m²
Thickness 0.060 ± 0.005 mm

GENERAL CHARACTERISTIC

1. Gloss and high transparent soft PVC Film.
2. Good tensile strength and tear resistance.

ADHESIVE **PE-05**

Type **Acrylic Emulsion**

PROPERTIES

Adhesion (S/Steel) ≥ 0.5 kg.f / 25 mm
Loop Tack 2.0 ± 0.5 psi.
End user temperature min.- 5°C max. 80°C
Providing range min -20 °C
Shelf life 1 year under optimum storage condition

GENERAL CHARACTERISTIC

1. Permanent type and high tack
2. Good adhesion to metal, plastic, paper, glass etc.
3. The adhesive complies with FDA 175.105 and approved for indirect contact food.
4. Anti-plasticizer migration adhesive.

LINER **GAWHOG58**

Type **Glassine Release Paper**

PROPERTIES

Basic Weight 58± 5 g/m²
Thickness 0.053 0.005 mm.
Color White

APPLICATION

1. High density
2. Excellent resistance in die-cut pressure.
3. Good transparency

APPLICATION

For labelling in applications where resistance against water, oil E.g. labelling toiletries, cosmetics, household product, advertising and other squeezable packages.

CAUTION

1. All technical data statements are typical and should not be used for specification purpose.
2. The Product must be stored in shady (or cool) place and do not expose to sunlight directly.
3. Before using, user shall determine the suitability of the product for their intended use.

Note : 1. Peel adhesion and Loop tack value are measured by ASTM, FINAT and JIS test method ones under control condition (23 ± 2°C, 65 ± 5%) and not guaranteed.

2. Substrates to be applied and methods of application may be distinguishable. You may contact us for more details through Technical Development Staff at technical@thaikk.co.th or call number + 662-338 4681-5