

TECHNICAL INFORMATION

PRODUCT : HSVLW : GLOSS WHITE PVC LABEL

VSWHOG70/PE-05/GAWHOG58

SURFACE **VSWHOG70**

Type	Gloss white soft PVC Film	
<u>PHYSICAL PROPERTIES</u>		<u>GENERAL CHARACTERISTIC</u>
Basic Weight	95± 5 g / m ²	1. High gloss white soft PVC Film
Thickness	0.070 ± 0.005 mm.	2. Good tensile strength and tear resistance.
		3. Thermal shrinkage of PVC is 4.5 %

ADHESIVE **PE-05**

Type	Acrylic Emulsion	
<u>PROPERTIES</u>		<u>GENERAL CHARACTERISTIC</u>
Adhesion (S/Steel)	≥ 6.0 N/25 mm	1. Permanent type and high tack
Loop Tack	11.2 ± 2.2 N/25 mm	2. Good adhesion to metal, plastic, paper, glass etc.
End user temperature	min. - 5°C max.80°C	3. The adhesive complies with FDA 175.105 and approved for indirect contact food.
Providing range	min -20 °C	4. Anti-plasticizer migration adhesive.
Shelf life	1 year under optimum storage condition	

LINER **GAWHOG58**

Type	Glassine Release Paper	
<u>PROPERTIES</u>		<u>APPLICATION</u>
Basic Weight	58± 5 g/m ²	1. High density
Thickness	0.053± 0.005 mm.	2. Excellent resistance in die-cut pressure
Color	White	3. Good transparency

APPLICATION

For labelling in applications where resistance against water, oil E.g. labelling toiletries, cosmetics, household product, advertising including heavy-duty chemicals and other squeezable packages.

CAUTION

1. All technical data statements are typical and should not be used for specification purpose.
2. The Product must be stored in shady (or cool) place and do not expose to sunlight directly.
3. Before using, user shall determine the suitability of the product for their intended use.

Note : 1. Peel adhesion and Loop tack value are measured by ASTM, FINAT and JIS test method ones under control condition (23 ± 2°C, 65 ± 5%) and not guaranteed.

2. Substrates to be applied and methods of application may be distinguishable. You may contact us for more details through Technical Development Staff at technical@thaikk.co.th or call number + 662-338 4681-5