

## TECHNICAL INFORMATION

PRODUCT : RF6002 : POLYPROPYLENE FILM RELEASED LINER

NO.	PHYSICAL PROPERTIES	UNIT	SPECIFICATION
1	Thickness	mm	$0.040 \pm 0.003$
2	Basic weight	$\text{g/m}^2$	$36 \pm 3$
3	Tensile strength	Kg	$\text{MD} \geq 5, \text{CD} \geq 12$
4	Release force	gf	$8 \pm 3$
5	Color	-	Transparent

Shelf-life                      1 year under optimum condition.

### Application

Polypropylene release liner is highly smooth, low shrinkage and clarity using for in a wide range of manufacturing processes including in the automotive and electronics industries.

### Caution

1. All technical data statements are typical and should not be used for specification purpose.
2. The Product must be stored in shady (or cool) place and do not expose to sunlight directly.
3. Before using, user shall determine the suitability of the product for their intended use.

---

Note : 1. Release force and Silicone coating weight value are measured by FINAT test method ones under control condition ( $23 \pm 2$  °C,  $50 \pm 5\%$ ) and not guaranteed.

2. Adhesive coating and method of application may be distinguishable. You may contact us for more details through Technical Development Staff at [technical@thaikk.co.th](mailto:technical@thaikk.co.th) or call number +662-338 4681-5