

TECHNICAL INFORMATION

PRODUCT : RPWD3001-55 : DOUBLE SIDE WHITE GLASSINE RELEASED LINER

NO.	PHYSICAL PROPERTIES	UNIT	SPECIFICATION
1	Basic weight	g/m ²	55 ± 5
2	Thickness	mm	0.053 ± 0.005
3	Tensile Strength	kg	MD ≥ 6, CD ≥ 3
4	Bursting	kg/cm ²	≥ 7
5	Release Force	gf	6 ± 2 / 5 ± 2
6	Silicone coating weight	g/m ²	1.2 ± 0.1/1.4 ± 0.1
7	Color	-	White

Shelf-life 1 year under optimum condition.

Application

Glassine release liner is highly smooth, transparency and density using for consumable products that have an adhesive coating, such as tapes, labels. Also they are used in a die cutting and sensor counting of manufacturing processes and double side coating application.

Caution

1. All technical data statements are typical and should not be used for specification purpose.
2. The Product must be stored in shady (or cool) place and do not expose to sunlight directly.
3. Before using, user shall determine the suitability of the product for their intended use.

Note : 1. Release force and Silicone coating weight value are measured by FINAT test method ones under control condition (23 ± 2 °C, 50 ± 5%) and not guaranteed.

2. Adhesive coating and method of application may be distinguishable. You may contact us for more details through Technical Development Staff at technical@thaikk.co.th or call number +662-338 4680-5