

## TECHNICAL INFORMATION

**Product Code : RPWDH4002**  
**Product Name : Double side white clay coated release paper**

NO.	PHYSICAL PROPERTIES	UNIT	SPECIFICATION
1	Basic weight	g/m <sup>2</sup>	120 ± 5
2	Thickness	mm	0.120 ± 0.010
3	Tensile Strength	kg	MD ≥ 5, CD ≥ 3
4	Bursting	kg/cm <sup>2</sup>	≥ 4
5	Release Force	gf	7 ± 2 / 6 ± 2
6	Silicone coating weight	g/m <sup>2</sup>	1.2 ± 0.1 / 1.2 ± 0.1
7	Color	-	White

**Shelf-life**                      1 year under optimum condition.

**Application**                      Typical uses of release liner using are consumable products that have an adhesive coating, such as tapes, labels, construction adhesives. Also they are used in a wide range of manufacturing processes including in the automotive and electronics industries.

**Caution**

1. All technical data statements are typical and should not be used for specification purposes.
2. The Product must be stored in a shady (or cool) place and not exposed to sunlight directly.
3. Before using, users shall determine the suitability of the product for their intended use.

*BY RESEARCH AND DEVELOPMENT (KK) SECTION (Revised: 2020)*

---

**Note** : 1. Release force and Silicone coating weight value are measured by FINAT test method ones under control condition (23 ± 2 °C, 50 ± 5%) and not guaranteed.  
 2. Adhesive coating and method of application may be distinguishable. You may contact us for more details through Technical Development Staff at [technical@thaikk.co.th](mailto:technical@thaikk.co.th) or call number +662-338 4681-5

